

Industrial S.B.C. specifications:

S.N.	Configuration of IPC2	Description, (P/N)
	Basic	IPC2
1	CPU	Haswell i7/2.1GHz/2C/4MB, (C4600) <i>or better</i>
2	DRAM [Low Voltage] Supported	16GB (2 x 8GB), Supported
3	Display and Graphics	Intel HD 4400 graphics (1x DisplayPort 1.2 up to 3200 x 2000 @60Hz 2 X HDMI 1.4a up to 4096 x 2304 @24 Hz)
4	HDD/SSD (Supported)	120 GB SSD 2.5", Supported
5	mSATA (Supported)	mSATA 256GB, Supported
6	WiFi & BT	WiFi a/c (2.4+5 GHz) + BT, (W8260)
7	OS (Supported)	Linux Mint, Supported
8	FACE Module	<ul style="list-style-type: none"> • Standard USB, Ethernet etc.
9	Power and Environmental Characteristics	<ul style="list-style-type: none"> • Unregulated 10-15VDC input • 6W-24W • Commercial, extended and Industrial operating temperature grades • Die Cast Aluminium, passive Cooling Fanless Design • 19cm x 16cm x 4cm (<i>max.</i>)
10	Cables and accessories	Power Supply, AC Cord, Serial Cable, HDMI/DVI Adapter, etc

Volker