

Sl. No	Details of Items*	Quantity
	<p data-bbox="427 190 1061 257">Paddy straw chopper / shredder cum spreader with following specifications</p> <ul style="list-style-type: none"> • Type: PTO driven • Power source: should work with tractor of 60 HP or less • Length of cutting bar: 1980 mm (min.) • Effective cutting width: 1950 mm (min.) • Diameter of reel: 450 mm (min.) • Width of reel: 1800 mm (min.) • Feeding augur to be provided with stone trap and beater • Chopping size: The chopping size is a function of diameter of bruising drum, number of blades on drum, overlapping of blades and rpm of drum. Hence the combination should be such that the machine can provide chopped straw size ≤ 7.5 cm of more than 65% of the chopped material. • Transport wheels: Pneumatic wheels with brand new tyres suitable for the machine • Weight: 1500 kgs (min.) <p data-bbox="475 750 678 784">Other requirements</p> <ul style="list-style-type: none"> • The machine should be able to cut the paddy stubble close to ground preferably less than 2.5" • The machine should be easily serviceable and spare parts available • The workmanship should be of high quality • The machine should not have any sharp edges • All moving parts should be covered/protected to avoid injuries • Machine should be painted with good quality paint after proper application of good quality primer • Machine warranty against manufacturing defects to be provided for a minimum of 1 year or more. 	01 Nos.